

HYYJ-502 Insulating Oil Tester



1.1 Functions

- 1) Breakdown test of user-defined
- 2) Proof test
- 3) IEC60156/IS6792/BS5874 test
- 4) ASTM D1816 standard test
- 5) ASTM D877 standard test
- 6) 5 minutes standard test
- 7) Manual test
- 8) Calibration interface for customers
- 9) Uploading data to PC and making word report automatically.
- 10) Result print

1.2 Technique index

- 1) Output voltage: AC 0V~100KV
- 2) Rate of voltage rise: 0.5kv/s \pm 5%, 2kv/s \pm 5%, 3kv/s \pm 5%, 5kv/s \pm 5%
- 3) Max test times setting for user-defined mode: 9
- 4) Stir time setting for user-defined mode: 0~999s
- 5) Waiting time setting for user-defined mode: 0~999s
- 6) Test error: 3%RDG+0.3%FS
- 7) Display: 256 \times 128 LCD
- 8) Maximum storage capacity: 100 groups of test data
- 9) Power supply : AC220V \pm 10%, 50Hz/60Hz
- 10) Environment temperature: 0~50 $^{\circ}$ C
- 11) Relative humidity \leq 80%RH
- 12) Weight 41kg
- 13) Size: 620 mm \times 430mm \times 330mm

